

TruDO Cables

TruDO® cables are designed to connect sensors and transmitters with improved performance, better repeatability and increased reliability in bioprocess applications such as cell culture and fermentation. The cables are available with a variety of standard connectors, and are also compatible with sensors made by other manufacturers.

TruDO™ cables are available with D4/T82 and VP connectors in 6 ft (2 m) and 10 ft (3 m) lengths.



D4/T82 Connection



VP 6.0 Connection



Features

- Optimum performance
- Designed for high performance
- Compatible with Broadley-James and Mettler Toledo
- Available with D4/T82 or VP connectors
- Lengths of 6ft (2 m) or 10 ft (3 m)

Specifications

DO	D4, T82 and VP connectors
Lengths	6 ft (2 m) and 10 ft (3 m)

DO Cables

D4/T82	VP
CAB-D4-06, 6 ft/2 m	CAB-VP-06, 6 ft/2 m
CAB-D4-10, 10 ft/3 m	CAB-VP-10, 10 ft/3 m

Finesse Solutions, LLC
3350 Scott Blvd, Bldg 1
Santa Clara, CA 95054

Finesse Solutions AG
Via Sogn Gieri 27a
CH-7402 Bonaduz
Switzerland

877-204-8644
www.finesse.com